



January 13, 2021

## **Tender Requirements T-2021-05**

The City of Dryden invites tenders to **supply one (1) New and Unused 2021 Municipal Floating Pontoon Dock**. Tender must include complete specifications for the proposed equipment. If the following requirements are not part of the manufacturer's standard equipment it must be added to meet the City of Dryden requirements.

### **Requirements**

<b>1.</b>	<b>Dock and Ramp Dimensions</b>	
	Dock is to be a minimum of 40 feet (12.2 metres) long by 10 feet (3 metres) Wide	Specify:
	Ramp is to be a minimum of 20 feet (6 metres) long by 8 feet (2.4 metres) wide	Specify:
	Meets or exceeds Ontario building codes for commercial load requirements	Specify:
<b>2.</b>	<b>Decking and Sideboard</b>	
	High density polyethylene decking	Specify:
	Mono- extruded, solid, one-piece material	Specify:
	Complete coverage, length and width	Specify:
	Sideboard cover on all four sides of dock	Yes:                  No:
	Decking color options	Please attach separate list
	Stainless steel hardware and deck screws	Yes:                  No:
	Through deck access hatches for securing dock to anchors	Yes:                  No:
	25-year warranty	Yes:                  No:
<b>3.</b>	<b>Pontoons and Mounts</b>	
	High density polyethylene pontoons with a min 0.5-inch thickness and 18- inch minimum diameter	Specify:
	High density polyethylene end caps fusion welded to pontoon with a minimum thickness of 1-inch	Yes:                  No:

	High density polyethylene mounting brackets fusion welded to pontoon with a minimum thickness of 1- inch	Yes:	No:
	Must be freeze in place safe, can stay in water year-round	Yes:	No:
	Must have a minimum sinking weight load of 95 lbs per linear foot	Specify:	
	Ultra-violet light protected	Yes:	No:
	Fully sealed and does not contain Styrofoam or expanded polystyrene	Yes:	No:
	Lifetime warranty	Yes:	No:
<b>4</b>	<b>Accessories and Attachments</b>		
	Commercial grade black dock edge bumpers to cover 3 sides of dock with stainless steel mounting hardware	Specify:	
	Commercial grade corner bumpers	Yes:	No:
	6 galvanized anchor cleats with a minimum weight rating of 500 lbs per cleat to anchor dock	Yes:	No:
	8 Black flip up dock cleats, low profile design to reduce tripping hazard	Yes:	No:
	All attachments and hardware required to anchor dock at shore to concrete abutment	Yes:	No:

**Tenders will not be accepted unless the above conditions are met, or equivalents are agreed upon with the Public Works Manager before tender.**